

**DIMMABLE | 24 V DC**

**HLG240**

**24 V ■ 240 W**  
Étanche  IP67  
Dimmable, 1-10V

Dimensions : 244 x 68 x 39 mm



**RÉF. RUBAL24240D**

**HLG320**

**24 V ■ 320 W**  
Étanche  IP 67  
Dimmable, 1-10V

Dimensions : 252 x 90 x 44 mm



**RÉF. RUBAL24320D**

**MDV200**

**24 V ■ 200 W**  
Dimmable, 1-10V

NON ÉTANCHE, dimensions : 207 x 76 x 35 mm



**RÉF. RUBAL24200**

**PBOX100D**

**24 V ■ 100 W**  
Dimmable, DALI / 1-10V / PUSH

NON ÉTANCHE, dimensions : 207 x 76 x 35 mm



**RÉF. PBOX100D**

**PBOX150D**

**24 V ■ 150 W**  
Dimmable, DALI / 1-10V / PUSH

NON ÉTANCHE, dimensions : 207 x 76 x 35 mm



**RÉF. PBOX150D**

**TL150**

**24 V ■ 150 W**  
Dimmable, TRIAC  
Étanche  IP66

Dimensions : 257 x 78 x 46 mm



**RÉF. RUBAL24150D**

**TF**

**24 V ■ 100 W**  
Dimmable, TRIAC

NON ÉTANCHE, dimensions : 210 x 67 x 34 mm



**RÉF. RUBAL24100D**

**TL40**

**24 V ■ 40 W**  
Dimmable, TRIAC

NON ÉTANCHE, dimensions : 180 x 60 x 36 mm



**RÉF. RUBAL2445D**

**PTEMC**

**24 V ■ 18 W**  
Dimmable, TRIAC

NON ÉTANCHE, dimensions : 165 x 41 x 28 mm



**RÉF. PTEMC24**

**MDR60**

**24 V ■ 60 W**  
Dimmable, 1-10V / PUSH

NON ÉTANCHE, dimensions : 206 x 51 x 36 mm



**RÉF. MDR60**