


HIGH BAY EVO2

QUALIKO^{srl}
PROFESSIONAL LIGHT COMPONENTS



Campane LED • LED High Bay



Inclination micro adjustment



Optional: Installation bracket Part N°: BCBRACKEVO2N



Type	Part N°	Dimensions (mm)	Input V	Weight kg	Flux (Lm)	° Kelvin	Power (W max)	Beam	CRI
HB EVO2 100	BC100EV2040N	Ø 338x165h	200÷240	4,50	12950	4000°K	100	110°	>80
HB EVO2 150	BC150EV2040N	Ø 338x165h	200÷240	5,00	18549	4000°K	150	110°	>80
HB EVO2 200	BC200EV2040N	Ø 338x165h	200÷240	5,50	25045	4000°K	200	110°	>80

Campana a LED IP65

- LED ad alta efficienza Lumileds
- Power Factor > 0,95
- Temperatura ambiente operativa -40°C÷+50°C
- Assenza di UV, IR, mercurio e sodio
- Accensione istantanea
- Applicazioni tipiche: magazzini, aree produttive, supermercati, palestre, lavorazione cibi, celle frigorifere, etc.

High power IP65 LED High Bay

- Lumileds high efficiency LED
- Power factor >0,95- No UV, IR, mercury or sodium
- Operating temperature -40°C÷+50°C
- Instant ON-OFF
- Typical applications: warehouse, manufacturing, floodlighting, gymnasium, food processing, cold storage, etc.

High power LED High Bay IP65

- High Brightness LED Lumileds
- Leistungsfaktor: >0,95
- Betriebstemperatur: -40°C÷+50°C
- Abwesenheit von UV, IR, Quecksilber und Natrium
- Sofortanschaltung
- Typische Anwendungen: Lagerhallen, Produktionsstätten, Supermärkten, Fitness Centre, Lebensmittelverarbeitung, Kühlhaus usw.

Suspension à LED haute efficacité IP65

- Facteur de puissance > 0,95 - LED Lumileds
- Anibsenca de UV, IR, mercure et sodium
- Température ambiante de fonctionnement -40°C÷+50°C
- Allumage immediate
- Applications: magasins, usines, supermarchés, gymnases, chambres frigorifiques, etc.

Campanas industriales con LED de alta potencia IP65

- Led Lumileds de alta eficiencia
- Factor de potencia > 0,95
- Temperatura de funcionamiento -40°C÷+50°C
- No UV, IR, Mercurio o sodio
- Encendido y apagado instantaneo
- Aplicaciones típicas: Almacenes, fábricas, supermercados, gimnasios, almacenes de frio, etc.

